



## Ideal cold air duct and improvement of cooling capacity in data centres

- energy cost savings up to 30 % for cooling
- modular construction
- expandable and retrofit without any problems
- applicable for corridors from 1000 to 1200 mm, or individual on request
- raised top construction (170 mm) enables additional mounting possibilities of 3 U rack and individual fixing of lightings or sensors
- optionally manual or automatic door opener
- no tools needed to remove glass roof pane for mounting or cleaning work

**Material:** sheet steel

**Finish:** RAL 9005 deep black /  
RAL 7035 light grey

**Delivery:**

assembled, mounting material included

*Optional:* full functionally wired

Following parts are available for the **modular construction:**

- Top unit for cabinet width 600mm or 800mm and corridors from 1000 up to 1200mm with toughened safety glass
- Two-part sliding door (manual operation) with toughened safety glass
- Two-part sliding door (automatic operation) with toughened safety glass
- Support bracket to fix lightings and sensors underneath glass roof
- Integrated 19" level 2x3U per roof element

**Contact us! We will be pleased to advise you on a conception for your custom-made housing.**



**apraNET** network technology division of apra-norm Elektromechnik GmbH

Gewerbegebiet · D-54552 Mehren · Phone: +49 (0) 65 92 95 12-0 · Fax: +49 (0) 65 92 95 12-50  
www.apranet.de · email: vertrieb@apranet.de

Subject to technical modifications