



Setup



KVM Switch

or



1 PC



8 or 16 PCs

OS Support
Win, Linux, FreeBSD

Computers
SPHD PS/2

LCD Monitor
17"

NEW OS Support
Vista

Rack Mount Kit	Depth (cm)
2X-010G (Long/Optional)	68 - 100
Short (Standard)	42 - 72

Easy Installation Rack Mount Kit	Depth (cm)
2X-012G (Long/Optional)	68 - 105
2X-011G (Short/Optional)	42 - 70

Features

- Integrated KVM console with 17" LCD monitor - in a Slideaway™ housing
- Slideaway™ housing is less than 1U - with top and bottom clearance for smooth operation in a 1U high system rack
- Internal power built in
- Adjustable depth to fit within the rack
- High video resolution:
 - Up to 1280 x 1024 @75Hz (17" LCD)
 - Supports DDC, DDC2, DDC2B
- DDC emulation of the LCD monitor - VGA settings of every connected computer are automatically adjusted for optimal output to the LCD monitor
- Language support: American English; UK English; German; French; Spanish; Traditional Chinese; Japanese; Korean
- Improved design-Single person installation (Optional)

Specifications

Function			CL1000
Connectors	KVM Ports	Keyboard/Video/Mouse	1 x SPHD-15 Female (Yellow)
	Power		1 x 3-prong AC Socket
Switches	LCM Adjustment		4 x Pushbuttons
	KM Reset		1 x Semi-Recessed Pushbutton
	Power		1 x Rocker
LEDs	Power		1 (Blue)
	Num Lock		1 (Green)
	Caps Lock		1 (Green)
	Scroll Lock		1 (Green)
Emulation	Keyboard / Mouse		PS/2
Video	17" LCD		1280 x 1024; DDC2B
I/P Rating			100 - 240 VAC; 50/60 Hz; 1A
Power Consumption	17" LCD		120V,27W / 230V,35W
Environment	Operating Temp.		0-40° C
	Storage Temp.		-20-60° C
	Humidity		0-80% RH, Non-condensing
Physical Properties	Housing		Metal
	Weight	17" LCD	13.70 kg
	Dimensions (D x W x H)		52.00 x 48.00 x 4.20 cm(19"1U)

* The specifications and pictures are subject to change without notice.

apraNET Geschäftsbereich Netzwerktechnik der apra-norm Elektromechnik GmbH

Gewerbegebiet · 54552 Mehren · Tel.: (0 65 92)95 12-0 · Fax: (0 65 92)95 12-50

www.apranet.de · email: vertrieb@apranet.de

Technische Änderungen vorbehalten

96

25.01.2008