



optiRACK

With the new wall mount distribution enclosure type optiRACK, network installation will be quite simple. The removable door and side panels provide an optimum accessibility inside the enclosure. In this manner the cabling can be easily done in the open frame and the assembling of the enclosure needs only a short time!

The delivery will be effected as a flat pack-version including mounting instruction.

An optical appreciation is the two-coloured design and the rounded angles. Standard the design-profile will be delivered in RAL 5014 (dove-blue), for a special coding or the customization (Corporate identity) we can also deliver several RAL-colours on request.

Delivery:

- 1 piece wall rack
- 2 side panels, screwed inside
- 1 front door with glass
- 1 19"-frame, depth variable
- 1 screw set M5 /for assembly of the 19"-components
- 1 earthing set

Delivery in flat pack !!!

class of protection: IP 40

colour:

enclosure:
RAL 7035 (light-grey)
design profiles:
RAL 5014 (dove-blue)

optiRACK wall mount distribution enclosure

H x W x D	U	Part no.
345 x 550 x 450	6	350-001-06
480 x 550 x 450	9	350-001-09
612 x 550 x 450	12	350-001-12

apraNET network technology division of apra-norm Elektromechanik GmbH

Gewerbegebiet · D-54552 Mehren · Tel.: +49 (0) 65 92 95 12-0 · Fax: +49 (0) 65 92 95 12-50
www.apranet.de · email: vertrieb@apranet.de

Subject to technical modifications

94

21.04.2009